

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29CFR 1910-1200.
Standard must be consulted for specific requirements.

Section I Product and Company Identification				
Product Name	Lee Instant Nail Glue			
Catalog No(s).	6901-000	Date Prepared	Revision	
		May 4, 2004	1	
Manufacturer/Address	Lee Pharmaceuticals 1434 Santa Anita Avenue South El Monte, CA 91733			
Emergency Telephone Numbers	Office: (800) 950-5337 24-hour: (800) 535-5053			
Chemical Name and Synonyms	Chemical Family	CAS No.	Molecular Formula	
NA	NA	7085-85-0	NA	
Section II Ingredients				
HAZARDOUS INGREDIENTS			OTHER INGREDIENTS	
Component	%	Threshold Limit Value (units)	Polymethyl Methacrylate EEC Cosmetic Approved Preservative	
Ethyl Cyanoacrylate	95-99%			
Section III Physical Data				
Boiling Point (°F)	150°F	Specific Gravity	1.04	
Vapor Pressure (mm Hg)	2mm Hg @ 133°F	Percent Volatile by Volume (%)	ND	
Vapor Density (Air = 1)	ND	Evaporation Rate (Water = 1)	Slower	
Solubility in Water	Insoluble	Other		
Appearance and Odor	Cloudy gel-like material with pungent odor			
Section IV Fire and Explosion Hazard Data				
Flash Point	181.4°F	Flammable Limits by Volume (%)	Lower ND	Upper ND
Fire Extinguishing Media	Dry Chemical; Carbon Dioxide; Foam			
Special Firefighting Procedure	Water will initiate polymerization process. Wear full self-contained breathing apparatus.			
Unusual Fire and Explosion Hazards	Flammable liquid			

Section V Health Hazard Data				
Routes of Entry	Inhalation Yes	Eyes Yes	Skin Yes	Ingestion No
Health Hazards (Acute or Chronic)	Acute: Eye irritation – BONDS SKIN INSTANTLY Chronic – Unknown			
Signs and Symptoms of Exposure	Irritation of eyes and mucous membranes			
Carcinogenicity	NTP? No	IARC Monographs? No	OSHA? No	
Medical Conditions Generally Aggravated by Exposure	None known			
Emergency and First Aid Procedures	Eye contact: Hold lid open and flush with water for 15 minutes and consult physician immediately. Skin Contact: Do not pull. Use acetone or glue remover. Inhalation: Move to fresh air and consult physician immediately. Ingestion: Consult physician immediately.			
Section VI Reactivity Data				
Stability	Stable Unstable	X	Conditions to Avoid	May harden and polymerize when exposed to heat or alcohol.
Incompatibility (Materials to Avoid)	Water, weak base, alcohols.			
Hazardous Decomposition Products	Acid, carbon monoxide, carbon dioxide, cyanide compounds			
Hazardous Polymerization	May Occur Will Not Occur	X	Conditions to Avoid	Heat
Section VII Spill or Leak Procedures				
Steps to be Taken in Case Material is Released or Spilled	Eliminate all sources of ignition. Evacuate area. Recover liquid material with absorbent material. Glue will harden. Remove and place in drum for disposal.			
Waste Disposal Method	Dispose according to Federal, State and Local regulations.			
Section VIII Special Protection Information				
Respiratory Protection (Specify Type)	Appropriate OSHA/MSHA approved respirator			
Ventilation	Local Exhaust	Yes	Special	
	Mechanical (General)	Yes	Other	
Protective Gloves	Polyethylene		Eye Protection	Safety Goggles
Other Protective Equipment	Eye bath, safety shower, chemical apron			
Section IX Special Precautions				
Precautions to be Taken in Handling and Storage	Keep container closed while not in use. Keep away from heat and flame. Store in a cool place.			
Other Precautions				